



APPLICATION FOR PERMIT FOR THE INSTALLATION
PIPE AND/OR UTILITY LINES WITHIN A COUNTY MAINTAINED
RIGHT OF WAY OR EASEMENT

Smith County Road & Bridge Department
P.O.Box 990
Tyler, Texas 75710

1. Applicant: _____ Date: _____
Company Name (if different): _____ Phone: _____
Address: _____ Fax: _____
_____ Zip: _____
24/7 Contact Name: _____ Phone: _____
Contractor: _____ Phone: _____
Bonding Company: _____ Phone: _____
2. Franchise Holder: _____ Phone: _____
3. Franchise Contact: _____ Phone: _____
4. Location (if applicable, length of installation in feet): _____

5. Type of work, location, and description of the proposed line and appurtenances is shown by 3 copies of drawings attached to this application. The line will be constructed and maintained on the County right-of-way as directed by the Road Administrator/Engineer in accordance with SMITH COUNTY specifications.

6. Describe all traffic controls or warning devices anticipated for this project: _____

7. Proposed start date: _____ Completion date: _____

It is expressly understood that the SMITH COUNTY Commissioners Court does not purport, hereby, to grant and right, claim, title, or easement in or upon this county road; and it is further understood that in the future should for any reason SMITH COUNTY should need to work, improve, relocate, widen, increase, add to or in any manner change the structure of this right-of-way, this line, if affected, will be moved under the direction of the SMITH COUNTY Road Administrator/Engineer and shall be relocated at the complete expense of the owner.

All work on the county right-of-way shall be performed in accordance with the Road Administrator/Engineer's instructions. The installation shall not damage any part of the road way.

Specific instructions and conditions are as follows:

1. **All underground lines are to be installed a minimum of 36 inches below flow line of the adjacent drainage or borrow ditch.**
2. **All buried lines carrying an electrical current, or electronic or optical signal shall have yellow plastic tape at least two inches in width, buried a minimum of twelve inches above such lines.**
3. Lines crossing under surfaced roads and under surfaced cross roads within the right-of-way shall be placed by boring. Boring shall extend from crown line to crown line.
4. All lines under roads carrying pressure in excess of 50psi shall be enclosed in satisfactory casing extending from right-of-way line to right-of-way line. Pipe used for casing may be any type approved by the Road Administrator and shall be capable of supporting the roadbed and traffic loads and shall be constructed such that there is no leakage through the casing, carrier pipe, joints or couplings. (Lines installed 48 inches or greater below flow line encasement is not required.)

